



## 220 Rolling Window

*Precision-calibrated rollers for long life and smooth fingertip operation*

### 220 Rolling

The 220 Kas-Kel Rolling Windows are built on precision-calibrated rollers for smooth fingertip operation and manufactured to last for years. Maximize natural light filtration indoors with a beautifully designed rolling window.

#### NFRC Thermal Performance Data\*

| GLAZING          | U-VALUE | SHGC | VLT  | CR | ZONE |
|------------------|---------|------|------|----|------|
| Energy Star U4   | 0.23    | 0.26 | 0.46 | 51 | N,NC |
| Energy Star III  | 0.28    | 0.36 | 0.51 | 59 | NC   |
| Low E w/ Argon   | 0.27    | 0.28 | 0.51 | 63 | N,NC |
| High Perf. Low E | 0.31    | 0.28 | 0.51 | 59 |      |
| Clear            | 0       | 0    | 0    | -  |      |

\*contact us to see thermal data with grids.

**KAS-KEL NEW CONSTRUCTION WINDOWS OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.**



### Features

|                  | STANDARD   | OPTION                              |                                     |
|------------------|--|-------------------------------------|-------------------------------------|
| <b>MATERIALS</b> | High-grade PVC                                     | <input checked="" type="checkbox"/> |                                     |
|                  | Fusion Welded Sash and Frame                       | <input checked="" type="checkbox"/> |                                     |
|                  | Sloped Sill and Interlock Leg                      | <input checked="" type="checkbox"/> |                                     |
|                  | Sash is easily removed for cleaning.               | <input checked="" type="checkbox"/> |                                     |
|                  | Aluminum Reinforced Meeting Rail                   | <input checked="" type="checkbox"/> |                                     |
| <b>PERF.</b>     | DP 35 Rating                                       | <input checked="" type="checkbox"/> |                                     |
|                  | DP 40 Rating                                       |                                     | <input checked="" type="checkbox"/> |
|                  | DP 50 Rating                                       |                                     | <input checked="" type="checkbox"/> |
| <b>GLAZING</b>   | Energy Star III                                    | <input checked="" type="checkbox"/> |                                     |
|                  | Energy Star U-4                                    |                                     | <input checked="" type="checkbox"/> |
|                  | Clear insulated glass (3/4")                       |                                     | <input checked="" type="checkbox"/> |
|                  | Duralite flexible, warm-edge spacers               | <input checked="" type="checkbox"/> |                                     |
|                  | Tints, Heat Reflection and other options available |                                     | <input checked="" type="checkbox"/> |
| <b>SCREENS</b>   | Aluminum Extruded Fiberglass 1/2 screen            | <input checked="" type="checkbox"/> |                                     |
|                  | Aluminum framed fiberglass full screen             |                                     | <input checked="" type="checkbox"/> |
|                  | Full Flex Screens                                  |                                     | <input checked="" type="checkbox"/> |
|                  | Aluminum Screening Material                        |                                     | <input checked="" type="checkbox"/> |
| <b>GRILLS</b>    | 3/4" Contoured Grill Between the Glass             |                                     | <input checked="" type="checkbox"/> |
|                  | 3/4" Contoured SDL with spacer bar                 |                                     | <input checked="" type="checkbox"/> |