

## 2200 Rolling Window

Built for long life and smooth fingertip operation

## **Kas-Kel Rolling Windows**

are built on precision-calibrated rollers for long life and smooth fingertip operation. ideal for porches, family rooms and multi-family dwellings. Sash is easily removed for cleaning.

## NFRC Thermal Performance Data\*

GLAZING	U-VALUE	SHGC	VLT	CR	ZONE
Energy Star U4	0.23	0.26	0.46	51	N, NC
Energy Star III	0.28	0.36	0.51	59	NC
Low E w/ Argon	0.27	0.28	0.51	63	N, NC
High Perf. Low E	0.31	0.28	0.51	59	NC
Clear	0	0	0	-	

<sup>\*</sup>contact us to see thermal data with grids.

**KAS-KEL REPLACEMENT WINDOWS WILL OFFER YOU A** LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.









operation		STANDARD	OPTION
	High-grade PVC delivers exceptional strength and thermal performance. White or Beige Interior	<b>⊘</b>	
MATERIALS	Fusion Welded Sash and Frame	<b>Ø</b>	
	Sloped Sill and Interlock Leg	<b>Ø</b>	
	Sash is easily removed for cleaning.		
PERFORMANCE	DP 35 Rating		
	DP 40 Rating		<b>Ø</b>
	DP 50 Rating		<b>Ø</b>
	Full 3" Foam insulating Wrap		<b>Ø</b>
GLAZING	Energy Star III (recommended) (¾")		
	Energy Star U-4 (¾")		<b>Ø</b>
	Clear insulated glass (3/4")		
	Duralite flexible, warm-edge spacers		
	Tints, Heat Reflection and other options available		<b>Ø</b>
SCREENS	Aluminum Extruded Fiberglass 1/2 screen		
	Aluminum framed fiberglass full screen		<b>Ø</b>
	Extruded Aluminum framed locking 1/2 Screen		<b>②</b>
	Aluminum Screening Material		<b>②</b>
GRILLS	5/8" Contoured Grill Between the Glass		
	3/4" Contoured SDL with spacer bar		<b>Ø</b>
HARDWARE	Smarter Rolling Windows are built on precision-calibrated rollers for long life and smooth fingertip operation. Sash is easily removed for cleaning.	•	
	Our Cam Locks are made of alloyed cast steel to stand up to frequent use.	•	
	All windows over 28 inches tall have 2 sash locks for maximum protection frame		
	Produced in white or beige to seamlessly match your window frame	<b>Ø</b>	
	Increased leverage assures a weather tight seal when locked	<b>Ø</b>	

