

performance you would expect to find in premium windows. Multiple point locking system with a clean fold away handle speaks volumes about our Casements. Configured with single or multi-unit combination for maximum ventilation. Fabricated for today's generation.

NFRC Thermal Performance Data*

GLAZING	U-FACTOR	SHGC	VLT	CR	ZONE
Energy Star U4	0.25	0.27	0.48	47	NC
Energy Star III	0.29	0.37	0.51	59	NC
Low E w/ Argon	0.28	0.28	0.51	63	NC
High Perf. Low E	0.32	0.28	0.51	58	N, NC
Clear	0	0	0	-	NC

^{*}contact us to see thermal data with grids.

KAS-KEL REPLACEMENT WINDOWS WILL OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.









		High-grade PVC delivers exceptional strength and thermal performance. White or Beige Interior		
	4LS	Equal lite top and bottom sash	Ø	
	MATERIALS	Full Fusion Welded Sash and Frame	Ø	
	MA	Sloped Sill and Interlock Leg	Ø	
		3-1/4" Frame Depth	Ø	
7	18	DP 40 Rating	Ø	
	PERF.	DP 50 Rating		Ø
		Full 3" Foam insulating Wrap		Ø
	3'4" GLAZING	Energy Star III		
		Energy Star U-4		Ø
		Clear insulated glass (3/4")		Ø
		Duralite flexible, warm-edge spacers		
		Tints, Heat Reflection and other options available		Ø
		Aluminum Extruded Fiberglass 1/2 screen		
	SCREENS	Aluminum framed fiberglass full screen		Ø
		Extruded Aluminum framed locking 1/2 Screen		②
		Aluminum Screening Material		Ø
	HARDWARE	Full Flex Screens		
		Our Cam Locks are made of alloyed cast steel to stand up to frequent use. (inferior vinyl windows have plastic locks)		
		All windows over 23 1/2 inches have 2 sash locks for maximum		
		Produced in white or beige to seamlessly match your window	Ø	
		Increased leverage assures a weathertight seal when locked		
		Night Latches		
		WOCD sash limiters		
	NO	Composite Reinforced Meeting Rail	②	
	CONSTRUCTIO	Bottom and Top Sash Tilt in for easy cleaning	Ø	
		Double weather stripped Meeting Rail	Ø	
	8	Full 3" Foam insulating Wrap		Ø
	GRILLS	5/8" Contoured Grill Between the Glass		
		3/4" Contoured SDL with spacer bar		

