



300C Series | Double Hung Window

High thermal efficiency - exceptionally solid design

The 300C Double Hung window utilizes a **New England Style 3 1/2" Cambridge Flat Casing** which integrates a built-in J-channel pocket for siding and nail-fin for installation. (filler available). An elegant, classic look and advanced design with high thermal ratings and glazing package options that meet or exceed Energy Star requirements.

Factory applied off the edge design ensures maximum weather protection.

GLAZING	U-VALUE	SHGC	VLT	CR	ZONE
Energy Star U4	0.25	0.27	0.48	47	N,NNC
Energy Star III	0.29	0.37	0.51	59	NC
Low E w/ Argon	0.28	0.28	0.51	63	NC
High Perf. Low E	0.32	0.28	0.51	58	
Clear	0	0	0	-	

**contact us to see thermal data with grids.*

KAS-KEL NEW CONSTRUCTION WINDOWS WILL OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.



Features

	STANDARD	OPTION
MATERIALS	High-grade PVC delivers exceptional strength and thermal performance. White or Beige Interior	<input checked="" type="checkbox"/>
	Full Fusion Welded Sash and Frame	<input checked="" type="checkbox"/>
	Sloped Sill and Interlock Leg	<input checked="" type="checkbox"/>
	3-1/4" Frame Depth	<input checked="" type="checkbox"/>
PERF.	DP 40 Rating	<input checked="" type="checkbox"/>
	DP 50 Rating	<input checked="" type="checkbox"/>
GLAZING	Energy Star III (recommended)	<input checked="" type="checkbox"/>
	Energy Star U-4	<input checked="" type="checkbox"/>
	Clear insulated glass	<input checked="" type="checkbox"/>
	Duralite flexible, warm-edge spacers	<input checked="" type="checkbox"/>
	Tints, Heat Reflection and other options available	<input checked="" type="checkbox"/>
SCREENS	Extruded aluminum framed fiberglass full screen	<input checked="" type="checkbox"/>
	Extruded aluminum framed locking 1/2 Screen	<input checked="" type="checkbox"/>
	Full Flex Screens on painted exterior frames	<input checked="" type="checkbox"/>
	Aluminum Screening Material	<input checked="" type="checkbox"/>
CONSTRUCTION	Composite Reinforced Meeting Rail	<input checked="" type="checkbox"/>
	Bottom and Top Sash Tilt in for easy cleaning	<input checked="" type="checkbox"/>
	Double weather stripped Meeting Rail	<input checked="" type="checkbox"/>
	3 1/2" Cambridge Casing	<input checked="" type="checkbox"/>
	Nailing fin with J Channel	<input checked="" type="checkbox"/>
	Nail Fin Only	<input checked="" type="checkbox"/>
	Egress Sizing Available	<input checked="" type="checkbox"/>
	Primed Solid Pine Applied Extension Jambes 4-9/16", 6-9/16" and Custom	<input checked="" type="checkbox"/>
Sheet Rock Returns	<input checked="" type="checkbox"/>	
HARDWARE	All windows over 23 1/2 inches have 2 sash locks for maximum protection	<input checked="" type="checkbox"/>
	Produced in white or beige to seamlessly match your window frame	<input checked="" type="checkbox"/>
	Night Latches	<input checked="" type="checkbox"/>
GRILLS	WOCD sash limiters	<input checked="" type="checkbox"/>
	5/8" Contoured Grill Between the Glass	<input checked="" type="checkbox"/>
	3/4" Contoured SDL with spacer bar	<input checked="" type="checkbox"/>