

300C Rolling Window

New England Style Cambridge Flat Casing

The 300C Rolling window utilizes a New England Style 3 ½" Cambridge Flat Casing which integrates a built-in J-channel pocket for siding and nail-fin for installation. (filler available). An elegant, classic look and advanced design with high thermal ratings and glazing package options that meet or exceed Energy Star requirements.

NFRC Thermal Performance Data*

| GLAZING | U-VALUE | SHGC | VLT | CR | ZONE |
|------------------|---------|------|------|----|------|
| Energy Star U4 | 0.23 | 0.26 | 0.46 | 51 | N,NC |
| Energy Star III | 0.28 | 0.36 | 0.51 | 59 | NC |
| Low E w/ Argon | 0.27 | 0.28 | 0.51 | 63 | N,NC |
| High Perf. Low E | 0.31 | 0.28 | 0.51 | 59 | |
| Clear | 0 | 0 | 0 | - | |

*contact us to see thermal data with grids.

KAS-KEL NEW CONSTRUCTION WINDOWS OFFER YOU A LIFETIME OF WORRY-FREE OPERATION, BACKED BY ONE OF THE BEST WARRANTIES IN THE INDUSTRY.



Features

| | STANDARD | OPTION | |
|------------------|--|--------|---|
| MATERIALS | High-grade PVC | ✓ | |
| | Fusion Welded Sash and Frame | ✓ | |
| | 3 ½" Cambridge Casing | ✓ | |
| | Sloped Sill and Interlock Leg | ✓ | |
| | Sash is easily removed for cleaning. | ✓ | |
| | Aluminum Reinforced Meeting Rail | ✓ | |
| PERF. | DP 35 Rating | ✓ | |
| | DP 40 Rating | | ✓ |
| | DP 50 Rating | | ✓ |
| GLAZING | Energy Star III | ✓ | |
| | Energy Star U-4 | | ✓ |
| | Clear insulated glass (3/4") | | ✓ |
| | Duralite flexible, warm-edge spacers | ✓ | |
| | Tints, Heat Reflection and other options available | | ✓ |
| SCREENS | Aluminum Extruded Fiberglass 1/2 screen | ✓ | |
| | Aluminum framed fiberglass full screen | | ✓ |
| | Full Flex Screens | | ✓ |
| | Aluminum Screening Material | | ✓ |
| GRILLS | 3/4" Contoured Grill Between the Glass | | ✓ |
| | 3/4" Contoured SDL with spacer bar | | ✓ |